

BSC series for filling of bored piles

BSC 1409 D

Concrete pressure up to 71 bar
Output up to 85 m³/h



Note: This is a merely informative, non-binding document. Maximum theoretical values listed. Specifications are subject to change without prior notice. Photos and drawings are for illustrative purposes only. For available options, please consult the factory.

Technical data

Dimensions		
Length	mm	5,310
Width	mm	1,900
Height	mm	2,245
Weight	kg	6,000
Concrete pump		
Output up to	m ³ /h	85
Concrete pressure up to	bar	71
Pump strokes	1/min	32
Delivery cylinder stroke	mm	1,400
Delivery cylinder diameter	mm	200
Pressure connection	m	5.5" (125)

Hopper		
Capacity	l	600
Max. noise level	dB	116
Central lubrication		
Rubber collar		
Chassis		
Engine Diesel Deutz, 6 cylinders		
Engine power	kW (HP)	129 (174)
Engine emissions Stage III A		
Steel crawlers, TFW-Fahrtechnik		
Max. speed	km/h	2
Diesel tank	l	135
Lights 2 on the hopper		

Technical data

Remote control		
Radio remote control (transport and output)		
Cable remote control (output)		
Cable length	m	10
Cleaning equipment		
Water tank	l	500
Cleaning pump	l/min /bar	50 / 20
Air compressor	l/min	860
Pressured air tank	l	40
Accessories		

Others		
Standard coat of paint MB 1227 Yellow		
Technical documents 1 paper copy, 1 CD-ROM		
Tool box		
Emergency button		
Electric vibrator		

Optionals

Automatic central lubrication
High pressure water pump
Radio remote control
Special coat of paint: doors, pipes and mud guard

Transport dimensions

